



- NOTE:
1. A QUALIFIED CONCRETE FINISHER MUST BE ON-SITE WHEN POURING CONCRETE.
 2. "CALIFORNIA CORNERS" OR STAMPED CONCRETE MAY BE USED ON THE PRIVATE CONCRETE SIDEWALK. THE PUBLIC SIDEWALK MUST HAVE A BROOM FINSH.
 3. PROVIDE 1/2" EXPANSION JOINTS AT 50' INTERVALS.
 4. DETECTABLE WARNINGS SHALL BE CAST-IN-PLACE TILES BY ADA SOLUTIONS, INC. AND SHALL BE DARK GRAY (FEDERAL COLOR #36118 OR APPROVED EQUAL)
 5. FILL ALL VOIDS IN ADJACENT TURF WITH 4" TOPSOIL AND SEED. SOD MAY BE REQUIRED BY THE VILLAGE FOR DISTURBED WIDTHS GREATER THAN 12".
 6. CARRIAGE WALK ACROSS THE STREET FROM A LOADING DOCK SHALL BE 8" THICK FOR THE ENTIRE WIDTH OF THE LOADING DOCK PLUS AN ADDITIONAL TEN FEET (10') ON EACH SIDE.

VILLAGE OF ELK GROVE VILLAGE

PCC SIDEWALK

