



ELK GROVE VILLAGE
GENERAL CONSTRUCTION NOTES

1. All work shall be in accordance with the applicable sections of the following specifications:
 - a. Illinois Department of Transportation (I.D.O.T.) "Standard Specifications for Road and Bridge Construction" (S.S.R.B.C.) latest edition.
 - b. "Standard Specifications for Water and Sewer Construction in Illinois" latest edition.
 - c. "Illinois Recommended Standards for Sewage Works" as published by the I.E.P.A.
 - d. The Metropolitan Water Reclamation District (M.W.R.D.) "Technical Guidance Manual for the Implementation of the Watershed Management Ordinance."
 - e. "Manual on Uniform Traffic Control Devices" (M.U.T.C.D.) latest edition.
 - f. The Subdivision and Development Codes and Standards of the Village of Elk Grove. (Chapter 8 of the Municipal Code)
 - g. "Illinois Urban Manual" published by the Association of Illinois Soil and Water Conservation Districts.
2. Contractor shall call J.U.L.I.E. at 1-800-892-0123 or 811 for utility locations **48 hours** before excavating.
3. The Elk Grove Village Community Development Department shall be notified **24 hours** in advance to schedule inspections for sidewalk, curb and gutter, driveways, aprons, paving, grading, watermain, sewer main utility services and landscaping. To schedule an inspection call (847) 357-4220.
4. Work shall not take place without required traffic control devices and barricades in place per the M.U.T.C.D. Any deficiency of safety or traffic control devices shall be just-cause to stop the project until such time as the deficiency is corrected.
5. Village streets shall not be closed without the written permission of the Elk Grove Village Community Development Department and then only after proper notification has been given to the Police and Fire Departments.
6. **The contractor shall immediately remove mud, soil or debris deposited on public streets.** Failure to keep streets clean shall be just-cause for issuance of a Stop Work Order or citation.

7. Signs located in the public right-of-way must not be removed or damaged. If a sign needs to be moved, notify the Public Works Department at (847) 734-8800.
8. Damaged parkway lawn areas and utility easement areas shall be restored with **4 inches of topsoil and sod**.
9. Construction materials shall not be stored within the Village right-of-way.
10. The owner/contractor shall be responsible for obtaining all required Federal, State, County, I.E.P.A. and M.W.R.D. permits prior to the issuance of a Village Construction Permit.
11. In the event pavement openings are required and approved by the Village, the opening shall be backfilled with crushed aggregate (CA-6) compacted in 12 inch lifts in accordance with Method 1, Article 550.07 of the S.S.R.B.C. **A Village inspector shall be present during the backfill operation.**
12. All pavement openings shall be saw cut before removal.
13. A permanent pavement repair, per Village Standard, shall be completed within seven (7) calendar days. Pavement opened to traffic prior to permanent repair shall be steel plated or cold patched with a minimum of 4 inches of bituminous material as directed by the Village.
14. All soil erosion and sedimentation controls shall be in-place before the start of any site work per the approved Erosion Control Plan.
15. All commercial and industrial driveway **Aprons** shall be eight (8) inch **Portland Cement Concrete** with 6'x 6"x #6 wire mesh on an eight (8) inch crushed aggregate base (CA-6). Framing shall be inspected prior to pouring.
16. **All detention basins in non-paved areas shall be sodded.**
17. All drainage ditches/swales shall be cleaned of all debris upon completion of the project.
18. Existing curb must be completely removed when depressed curb is installed. The "sawing off" of the top of curb is prohibited.